


### SC Adapter



### Features

- SC Adapter Meets Latest TIA/EIA 604-3, JIS C5973, IEC Specification
- Included dustcaps
- Available with phosphorous bronze sleeve for singlemode or multimode use or zirconia ceramic sleeve for singlemode use
- Available with plastic or metal housing

### Specification

Item	Description
Insertion Loss	< 0.3 dB
Exchangeability	< 0.2 dB
Repeatability	< 0.2 dB
Operational Temperature	- 40°C ~ + 70°C
Storage Temperature	- 40°C ~ + 70°C

### Ordering Information

Part Number	Description
LTOC-ADP-SC-MMDX-B	Fiber Adapter MM SC Duplex - Bronze
LTOC-ADP-SC-MMDX-C	Fiber Adapter MM SC Duplex - Ceramic
LTOC-ADP-SC-SMDX-B	Fiber Adapter SM SC Duplex - Bronze
LTOC-ADP-SC-SMDX-C	Fiber Adapter SM SC Duplex - Ceramic
LTOC-ADP-SC-MMSX-B	Fiber Adapter MM SC Simplex - Ceramic
LTOC-ADP-LC-MMSX-C	Fiber Adapter MM SC Simplex - Ceramic
LTOC-ADP-SC-SMSX-B	Fiber Adapter SM SC Simplex - Bronze
LTOC-ADP-SC-SMSX-C	Fiber Adapter SM SC Simplex - Ceramic