

RF JUMPER

::: Product Overview :::



Cable Type	Connector A	Connector B	Length	Attenuation, MHz, dB				VSWR (Return Loss), GHz			IM3 dBc	Part Number	
				450	900	1800	2400	0.8-1.0	1.7-2.0	2.0-2.4			
1/4" Flexible	N Male/Female 7/16 Male/Female	N Male/Female 7/16 Male/Female	1.5m	0.18	0.26	0.39	0.45	1.06(30)	1.08(28)	1.08(28)	-155	LJRF- 803M 803M 804F 804F 703M 703M 704F 704F	-01SF - XX
			2.0m	0.24	0.35	0.52	0.6	1.06(30)	1.08(28)	1.08(28)	-155		
			3.0m	0.36	0.52	0.78	0.9	1.06(30)	1.08(28)	1.08(28)	-155		
			5.0m	0.6	0.87	1.3	1.5	1.06(30)	1.08(28)	1.08(28)	-155		
3/8" Flexible	N Male/Female 7/16 Male/Female	N Male/Female 7/16 Male/Female	1.5m	0.14	0.2	0.29	0.34	1.06(30)	1.08(28)	1.08(28)	-155	LJRF- 803M 803M 804F 804F 703M 703M 704F 704F	-02SF - XX
			2.0m	0.18	0.26	0.38	0.45	1.06(30)	1.08(28)	1.08(28)	-155		
			3.0m	0.27	0.39	0.58	0.68	1.06(30)	1.08(28)	1.08(28)	-155		
			5.0m	0.46	0.66	0.96	1.13	1.06(30)	1.08(28)	1.08(28)	-155		
1/2" Flexible	N Male/Female 7/16 Male/Female	N Male/Female 7/16 Male/Female	1.5m	0.11	0.16	0.23	0.27	1.06(30)	1.08(28)	1.08(28)	-155	LJRF- 803M 803M 804F 804F 703M 703M 704F 704F	-03SF - XX
			2.0m	0.14	0.21	0.31	0.36	1.06(30)	1.08(28)	1.08(28)	-155		
			3.0m	0.22	0.32	0.47	0.54	1.06(30)	1.08(28)	1.08(28)	-155		
			5.0m	0.36	0.53	0.78	0.91	1.06(30)	1.08(28)	1.08(28)	-155		
1/4" Corrugated	N Male/Female 7/16 Male/Female	N Male/Female 7/16 Male/Female	1.5m	0.14	0.2	0.3	0.35	1.06(30)	1.08(28)	1.08(28)	-155	LJRF- 803M 803M 804F 804F 703M 703M 704F 704F	-01C - XX
			2.0m	0.19	0.27	0.39	0.46	1.06(30)	1.08(28)	1.08(28)	-155		
			3.0m	0.28	0.41	0.59	0.69	1.06(30)	1.08(28)	1.08(28)	-155		
			5.0m	0.47	0.68	0.99	1.15	1.06(30)	1.08(28)	1.08(28)	-155		
3/8" Corrugated	N Male/Female 7/16 Male/Female	N Male/Female 7/16 Male/Female	1.5m	0.1	0.15	0.21	0.25	1.06(30)	1.08(28)	1.08(28)	-155	LJRF- 803M 803M 804F 804F 703M 703M 704F 704F	-02C - XX
			2.0m	0.14	0.2	0.29	0.33	1.06(30)	1.08(28)	1.08(28)	-155		
			3.0m	0.2	0.29	0.43	0.5	1.06(30)	1.08(28)	1.08(28)	-155		
			5.0m	0.34	0.49	0.71	0.84	1.06(30)	1.08(28)	1.08(28)	-155		
1/2" Corrugated	N Male/Female 7/16 Male/Female	N Male/Female 7/16 Male/Female	1.5m	0.07	0.1	0.15	0.17	1.06(30)	1.08(28)	1.08(28)	-155	LJRF- 803M 803M 804F 804F 703M 703M 704F 704F	-03C - XX
			2.0m	0.09	0.14	0.2	0.23	1.06(30)	1.08(28)	1.08(28)	-155		
			3.0m	0.14	0.2	0.3	0.35	1.06(30)	1.08(28)	1.08(28)	-155		
			5.0m	0.24	0.34	0.5	0.58	1.06(30)	1.08(28)	1.08(28)	-155		